

INSTALLATION INSTRUCTIONS
FOR INSTALLING RUBBER SEAL TO COUNTER
ICE COOLED DISPENSER
(15 x 23, 23 x 23, and 30 x 23 DROP-INS)

1. BEFORE INSTALLING RUBBER SEAL

1.1 Counter top should be clean and free of debris. If necessary, clean with a mild detergent and water.

NOTE

Insure counter top is dry before installation of the rubber sponge seal.

2. INSTALLATION

CAUTION

RUBBER SPONGE SEAL MUST BE INSTALLED BEFORE DISPENSER IS DROPPED IN TO COUNTER CUTOUT.

2.1 Apply self-adhesive rubber sponge seal (PN 02-0507) along cut edge of the counter footprint cutout.

NOTE

Installation of rubber sponge seal will prevent liquid from seeping through footprint cutout and leaking to the floor.

Check out the Lancer web site:
www.lancercorp.com

LANCER

6655 LANCER BLVD. • SAN ANTONIO, TEXAS 78219 USA • (210) 310-7000

FAX SALES

• USA-CANADA – 210-310-7250 • LATIN AMERICA – 210-310-7245 • ASIA – 210-310-7242 •
• EUROPE – 32-2-755-2399 • PACIFIC – 61-8-8268-1978 •

FAX ENGINEERING: • 210-310-7096

"Lancer" is the registered trademark of Lancer • Copyright — 1996 by Lancer, all rights reserved.

DATE: 08/12/96
P.N.: 28-0640